

An ISO 9001:2015 Company



ON AIR WARNING SIGN

ON AIR LIGHT SD-11X5

ON AIR LIGHT

DIGI-SYS ON AIR SD-11X5 is the most popular on air warning sign units. The unit has practically decades of trouble free life expectancy. This is due to use of Hi bright LED's as light source. There are more than hundred specially selected LED's used to give uniform and bright back light.

- HIGH QUALITY DESIGN
- GREAT PERFORMANCE
- COST EFFECTIVE
- LONG LIFE
- GOOD EFFICENCY



ON AIR LIGHT SD-11X5

Salient Features

- Fully solid state
- Long life LED bulbs
- Excellent visibility
- In built Isolation Relay 12 Volts
- Internal isolated 12V supply for relay
- Custom legends available
- Easy and neat fixing on Wall

Application

- Studio warning Lights
- Transmission warning signs
- Radio stations
- Transmitter stations
- Recording studios
- News Channels
- Conference Halls
- Talk back Circuits
- Media centers

DIGI-SYS ON AIR SD-11X5 is the most Popular on air warning sign units. The unit has practically Decades of trouble free life expectancy. This is due to use of Hi bright LED's as light source. There are more than hundred specially selected LED's used to give uniform and bright back light. The diffuser system used is a high quality translucent phenolic panel. There is a strong clear back printed acrylic front sheet provide years of excellent look.

ON AIR lights are available in wall mount or hanging versions. The unit is made of sturdy metal body and powder coated in Black as standard. The design includes space to accommodate loose ends of connecting wires. There are two Eye holes at the back for flush mounting it on the wall. Versions are available for 230 volts and 110 volts or automatic voltage selection.





Technical Specification

Input

Operating Voltage
 Light source
 Readable distance
 Control eliment
 110/230 volts AC
 Hi bright LED's
 2 to 50 Mtrs
 Sealed Relay

• Coil resistance 620 ohms

• Coil Voltage 5-24 volts (Standard 12 v supply for relay available)

Other

Size- HxWxD
 Power
 63.5mm X279.4mmX158.75mm (1.75"x8.5"x6.25")
 110/230V ±10%, 60/50Hz ±4%, 20 VA max

Internal Interface connection

Passive contact closer

- External 12 volts switched
- External open collector NPN
- Any other external switching voltage



Why Choose DIGI-SYS

DIGI-SYS Your innovative idea's need products which can meet new challenges and compliment your efforts. Our in house innovative end to end computer aided design and manufacturing process is the best solution to meet critical timelines. Our artificial intelligence integrated in every product design, provides unmatched flexibility in field to configure our products to critical demanding needs and yet are very simple to operate. But technology and human innovation know no scarcity.

Our marketing and sales is bonded to customer support. Our technical experts assist you in system design as part of our product offering, which is optimised to your needs. In other words our support starts even before you buy a product from us. Our goal is to provide you best solution for your needs rather than sell you what we have in stock. Prospects who show interest in our products and services invariably get rewarded with best solution at most cost effective price.

Our Products Line

- Pro Audio Monitor
- Analog to Digital & Digital to analog Audio Converter
- Audio Router
- Remote Site Controller
- Audio Distributor/Switcher
- ON-AIR Light
- Audio Console Mixer
- FM Power Divider/Combiner
- Convection Dummy load (DC to 300 Mhz

For further information, Please contact us at:

DIGITAL SYSTEM SOLUTION
ISO 9001 : 2015 Registered
16192 Coastal Hwy, Lewes, DE 19958, USA,
sales@digisysltd.com | www.digisysltd.com

Phone: +1 302-604-7089